

## C-680 FlatJet Printer



- **Manual paper feed of single documents**
- **Self-controlled document alignment**
- **Sensor controlled and secure handling of all forms and documents**
- **User-friendly operation**
- **Optional sheet feeder (250 pages)**
- **High print quality (max. 4800dpi)**

Spezification	C-680
<b>Printing System</b>	Thermal InkJet Flatbed
<b>Print Head</b>	416 nozzles for black, 300 nozzles for colour
<b>Print Speed</b>	max. 12 pages/minutes
<b>Resolution</b>	1200dpi black 4800dpi colour
<b>Memory</b>	8 MB RAM
<b>Media Size</b>	Manual feeder width: 55mm – 230mm, length: 70mm – 600mm Optional sheet feeder (250 pages) width: 210mm – 220mm, length: 180mm – 360mm
<b>Paper Supply</b>	Sensor controlled and manual operated flatbed feeding with automatic document alignment and edge finding
<b>Paper Thickness</b>	Max 1.5mm
<b>Paper Types</b>	letter, envelopes, label, CD ROM cover, passbooks, coated plastic cards
<b>Ink Reservoir</b>	black 19ml, tri colour 17ml
<b>Emulation</b>	HP PCL Level 3 Enhanced, ASCII
<b>Interface</b>	IEE 1284 Centronics / Parallel bi-directional USB (kompatibel USB 2.0) Ethernet 10/100/1000, TCP/IP (optional)
<b>Character Fonts</b>	8 character fonts (4 landscape and portrait formats) CG Times, CG Times Italic, Univers, Univers Italic, Courier, Courier Italic, Letter Gothic Italic
<b>Noise</b>	< 40dB(A)
<b>Power Consumption</b>	32V/1A (external power supply)
<b>Dimension/Weight</b>	Printer: 447 (W) x 145 (H) x 235 (D) mm / 7 kg Printer with sheet feeder: 447 (W) x 207 (H) x 382 (D) mm / 10 kg
<b>Operating System</b>	MS 2000, XP
<b>Warranty</b>	2 years warranty (bring-in)
<b>Certifications</b>	CE
<b>Lifetime</b>	50.000 pages

Specifications are subject to change without notice. All registered trademarks are the property of their respective companies.