

### **EZ-1000 Plus Series**

### **Direct Thermal / Thermal Transfer Label Printer**



- **32 bit CPU**
- **USB 2.0 Port Standard**
- **Enhance features**
- **Options for your choice**

# THERMAL LABEL PRINTER

## EZ1000Plus Series Product Specifications

Model	EZ-1100 Plus	EZ-1200 Plus	EZ-1300 Plus
<b>Resolution</b>	203 dpi (8 dot/mm)	203 dpi (8 dot/mm)	300 dpi (12 dot/mm)
<b>Print Mode</b>	Thermal Transfer / Direct Thermal		
<b>CPU</b>	32 Bit		
<b>Memory</b>	4 MB Flash, 16 MB SDRAM		
<b>Print Speed</b>	2" ~ 4"	2" ~ 6"	2" ~ 4"
<b>Print Length</b>	min. 12mm (0.47") max. 1727mm (68")	min. 12mm (0.47") max. 1727mm (68")	min. 12mm (0.47") max. 762mm (30")
<b>Print Width</b>	108mm (4.25")	108mm (4.25")	105.7mm (4.16")
<b>Sensor Type</b>	Adjustable Reflective Sensor / fixed transmissive, center aligned		
<b>Sensor Detection</b>	Type: Label gap and black mark sensing Detection: Label length auto sensing and / or program command setting		
<b>Media</b>	Label Roll Outer Diameter: max. 125mm (4.92") Core Diameter: 25.4mm (1"), 38.1mm (1.5"), 76.2mm (3") Width: 25.4mm (1") ~ 118mm (4.64") Thickness: 0.06mm ~ 0.25mm (0.0025"~0.0098")		
<b>Ribbon</b>	Length: 300m (981ft) Ribbon Roll Outer Diameter: max. 68mm (2.67") Ribbon Width: 30mm ~ 110mm (1.18" ~ 4.33") Coating: nur außen Core Inner Diameter: 25.4mm (1") Ribbon Type: wax, wax/resin, resin		
<b>Printer Language</b>	EZPL (Firmware downloadable)		
<b>Software</b>	Application: QLabel-IV (EZPL only) DLL & Driver: Microsoft Windows NT 4.0, 2000, XP, Vista		
<b>Resident Fonts</b>	11 resident alphanumeric Fonts (included OCR A & B), 8 times expandable (horizontally, vertically) Bitmapped Fonts and scalable Fonts (Code Page 850 & 852) are rotatable at 90°		
<b>Fonts Download</b>	Windows Bitmap Fonts are rotatable at 90° True-Type Fonts (Ver. 2.XX) and Asian Fonts are rotatable at 90°		
<b>Image Handling</b>	BMP, PCX; Support ICO, WMF, JPG, EMF file through software		
<b>Barcode</b>	Code 39, Code 93, Code 128 (subset A,B,C), UCC/EAN-128 K-Mart, UCC/EAN-128, UPC A / E (add on 2 & 5), I 2 of 5, I 2 of 5 with Shipping Bearer Bars, EAN 8 / 13 (add on 2 & 5), Codabar, Post NET, EAN 128, DUN 14, MaxiCode, HIBC, Plessey, Random Weight, Telepen, FIM, China Postal Code, RPS 128, PDF417, Datamatrix code & QR code		
<b>Interface</b>	Serial Port: RS-232 (Baud Rate: 4800 ~ 115200, Xon / Xoff, DSR / DTR) USB Port: V2.0 Parallel Port: Bi-Direction		
<b>Control Panel</b>	Two multiple-color LED lights: READY, STATUS Function Key: FEED		
<b>Power</b>	Auto Switching 100/240 VAC, 50/60 Hz		
<b>Real Time Clock</b>	Standard		
<b>Environment</b>	Operation: 5°C ~ 40°C (41°F ~ 104°F) Storage: -20°C ~ 50°C (-4°F ~ 122°F)		
<b>Humidity</b>	Operation: 30-85%, non-condensing, free air Storage: 10-90%, non-condensing, free air		
<b>Cert. Approval</b>	CE, BSMI, FCC Class A, CB, CUL, GS, CCC		
<b>Printer Dimension</b>	Length: 285mm (11.2") Height: 171mm (6.8") Width: 226mm (8.9") Weight: 2.72kg		
<b>Options</b>	Rotary Cutter Module Stripper Module Socket for CompactFlash Memorycard with Real Time Clock Internal Ethernet Adapter Card		
<b>Packing</b>	USB cable, Power cable, Parallel cable, Ribbon, Ribbon Shaft (1" Core), Empty Ribbon Core, Label, Label Roll Core, CD, Quick Start Guide, Cleaning Card		

Specifications are subject to change without notice. All registered trademarks are the property of their respective companies.