

EZ-DT-2 / -DT-4

Direct Thermal Label Printer



- **32 Bit CPU**
- **Direct Thermal Mode only**
- **203 dpi THP**
- **USB 2.0 Standard / Serial**
- **Printing speed up to 4 IPS**
- **Wall-mounted Feature**

THERMAL LABEL PRINTER

EZ-DT-2 Product Specifications

Model	EZ-DT-2	EZ-DT-4
Resolution	203 dpi (8 dot/mm)	
Print Mode	Direct Thermal	
CPU	32 Bit	
Memory	4 MB Flash, 8 MB SDRAM	4 MB Flash, 8 MB SDRAM 8 (with RTC)
Print Speed	2" ~ 4"	
Print Length	min. 12.7mm (0.5") / max. 1727mm (68")	
Print Width	max. 54mm (2.12")	max. 108mm (4.25")
Sensor Type	Adjustable Reflective Sensor / fixed transmissive, center aligned	
Sensor Detection	Type: Label gap and black mark sensing Detection: Label length auto sensing and / or program command setting	
Media	Label Roll: max. 127mm (5") Core Diameter: 25.4mm (1") / 38.1mm (1.5") Width: 15mm (0.6") ~ 60mm (2.36") Thickness: 0.06mm ~ 0.20mm (0.0025"~0.0079")	Label Roll: max. 127mm (5") Core Diameter: 25.4mm (1") / 38.1mm (1.5") Width: 25mm (1") ~ 118mm (4.65") Thickness: 0.06mm ~ 0.20mm (0.0025"~0.0079")
Printer Language	EZPL; option EPL2 (Firmware downloadable)	
Software	Application: QLabel-IV (EZPL only) DLL & Driver: Microsoft Windows NT 4.0, 2000, XP, Vista	
Resident Fonts	11 resident alphanumeric Fonts (included OCR A & B), 8 times expandable (horizontally, vertically) Bitmapped Fonts and scalable Fonts (Code Page 850 & 852) are rotatable at 90°	
Fonts Download	Windows Bitmap Fonts are rotatable at 90° True-Type Fonts (Ver. 2.XX) and Asian Fonts are rotatable at 90°	
Image Handling	BMP, PCX; Support ICO, WMF, JPG, EMF file through software	
Barcode	Code 39, Code 93, Code 128 (subset A,B,C), UCC/EAN-128 K-Mart, UCC/EAN-128, UPC A / E (add on 2 & 5), I 2 of 5, I 2 of 5 with Shipping Bearer Bars, EAN 8 / 13 (add on 2 & 5), Codabar, Post NET, EAN 128, DUN 14, MaxiCode, HIBC, Plessey, Random Weight, Telepen, FIM, China Postal Code, RPS 128, PDF417, Datamatrix code & QR code	
Interface	Serial Port: RS-232 (Baud Rate: 4800 ~ 115200, Xon / Xoff, DSR / DTR) USB Port: V2.0	
Control Panel	One Tri-color LED: Power (Red, Orange, Green) Function Key: FEED	
Power	Auto Switching 100/240 VAC, 50/60 Hz	
Real Time Clock	Standard	
Environment	Operation: 5°C ~ 40°C (41°F ~ 104°F) Storage: -20°C ~ 50°C (-4°F ~ 122°F)	
Humidity	Operation: 30-85%, non-condensing, free air Storage: 10-90%, non-condensing, free air	
Cert. Approval	CE, BSMI, FCC Class A, CB, CUL, GS, CCC	
Printer Dimension	Length: 218mm (8.5") Height: 172mm (6.77") Width: 100mm (3.94") Weight: 1.2kg	Length: 218mm (8.5") Height: 166mm (6.53") Width: 168mm (6.61") Weight: 1.5kg
Options	Guillotine Cutter Module Stripper Module Internal Ethernet Adapter Card	Guillotine Cutter Module Stripper Module Internal Ethernet Adapter Card
Packing	USB cable, Power cable, CD, Quick Start Guide, Cleaning Card	

Specifications are subject to change without notice. All registered trademarks are the property of their respective companies.

Godex Europe GmbH

Arnhäuschen 36

42929 Wermelskirchen, Germany

Tel.: +49 (0)2193 53396-0 eMail : info@godex.eu

Fax: +49 (0)2193 53396-69 Internet : http://www.godex.eu



08-2007